This version issued: October, 2022

Phone: 1300 336 333

Section 1 - Identification

Bluesea Technologies Pty Ltd

Level 8, 80 George Street

Parramatta NSW 2150 AUSTRALIA

Chemical nature: Lubricant packaged as an aerosol spray.

Trade Name: NanoGuard Ultimate Armour IWRC Aerosol

Product Use: Lubricant spray.

Creation Date: October, 2022

This version issued: October, 2022 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

SUSMP Classification: None allocated.

ADG Classification: Class 2.1: Flammable gases.

UN Number: 1950, AEROSOLS







Phone: 1300 336 333

GHS Signal word: DANGER

Flammable aerosols Category 1

Skin Corrosion /Irritation Category 2

Specific Target Organ toxicity - repeated exposure Category 2

HAZARD STATEMENT:

H222: Extremely flammable aerosol

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P241: Use explosion-proof electrical equipment.

P251: Do not pierce or burn, even after use.

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P314: Get medical advice or attention if you feel unwell.

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P332+P313: If skin irritation occurs: Get medical advice.

P372: Explosion risk in case of fire.

P381: Eliminate all ignition sources if safe to do so.

P370+P378: In case of fire: Use carbon dioxide, dry chemical, foam, water fog, to extinguish.

STORAGE

P402: Store in a dry place.

P410+P412: Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

SAFETY DATA SHEET

Issued by: Bluesea Technologies Pty Ltd

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

This version issued: October, 2022

Phone: 1300 336 333

Emergency Overview

Physical Description & Colour: Grey liquid.

Odour: Characteristic odour.

Section 3 – Composition and Information on Ingredients				
Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Aromatic hydrocarbons	64742-94-5	~40	not set	not set
Alkanes, C3-4	68475-59-2	<60	not set	not set
Petroleum distillates	-	3-15	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Quickly and gently blot away excess liquid. Seek urgent medical attention. Flush contaminated area with lukewarm, gently flowing water for at least 60 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

Eye Contact: Quickly and gently blot material from eyes. No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

Ingestion: If nausea or gastric upset develops, remove individual to rest area and monitor. If symptoms get worse or if individual becomes distressed, do NOT induce vomiting. Contact the Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: Extremely flammable aerosol. Pressurised container: may burst if heated. The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a significant risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should evacuate the area and take appropriate precautions. Fires involving significant quantities of aromatic hydrocarbons often generate large clouds of black smoke. The smoke and other pyrolysis products may be toxic.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam or water fog. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus. Cool closed, undamaged containers exposed to fire with water spray.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC and Nitrile. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

SAFETY DATA SHEET

Issued by: Bluesea Technologies Pty Ltd

STEL (mg/m³)

Page: 3 of 6

This version issued: October, 2022

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions e.g. use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10. Take special care if handling this product over extended periods as it is a cumulative poison.

Storage: Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC, nitrile.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Grey liquid.

Odour: Characteristic odour.

Freezing/Melting Point: No specific data. Liquid at normal temperatures.

Boiling Point:

Flash point:

Upper Flammability Limit:

Lower Flammability Limit:

Not available

Not available

Not available

Flammability Class: Aerosols category 1 (GHS) - extremely flammable aerosol.

Volatiles:
Vapour Pressure:
No data.
Vapour Density:
No data.
Specific Gravity:
No data.
Water Solubility:
pH:
No data.
Volatility:
No data.

SAFETY DATA SHEET

Issued by: Bluesea Technologies Pty Ltd Phone: 1300 336 333

Page: 4 of 6

This version issued: October, 2022

Odour Threshold: No data.

Evaporation Rate: No data.

Coeff Oil/water Distribution: No data

Particle Characteristics: Not applicable for liquids.

Autoignition temp: No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Containers should be kept dry. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Toxicity: Ingestion of liquid hydrocarbon has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea. Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure.

Owing to its low viscosity and low surface tension, some short chain liquid hydrocarbons pose a risk of aspiration into the lungs following oral exposure. A few mL of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30mL may be fatal.

Prolonged dermal exposure, e.g., resulting from wearing clothes that have been soaked or moistened for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to short chain liquid hydrocarbons at high levels. However, owing to lack of details and the sporadic nature of the reportings, the relevance of these findings is unclear.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity but are CNS depressants and have a disinhibiting euphoric effect.

Classification of Hazardous Ingredients

Ingredient Health Hazard Statement Codes

Alkanes, C3-4 H220, H330, H350, H340, H319, H315, H335, H372, H360Df

- Gases under pressure
- Flammable gas category 1
- Acute toxicity category 2
- Carcinogenicity category 1A
- Germ cell mutagenicity category 1B
- Eye irritation category 2A
- Skin irritation category 2
- Specific target organ toxicity (single exposure) category 3
- Specific target organ toxicity (repeated exposure) category 1
- Reproductive toxicity category 1B

NOTE: Some of the above classifications relate to impurities found in some grades of ingredients. These do not apply in situations where impurities are not present at hazardous concentrations.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

SAFETY DATA SHEET

Issued by: Bluesea Technologies Pty Ltd Phone: 1300 336 333

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

This version issued: October. 2022

Short Term Exposure: Major health effect from this product is misuse of the aerosol function. If sprayed

continuously on skin or in eyes, it can cause frostbite.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause

damage through frostbite.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. This product, while believed to be not harmful, is likely to cause headache and gastric disturbance such as nausea and vomiting if ingested in significant quantities. This product is unlikely to cause any irritation problems in the short or long term.

Long Term Exposure: Long term minor exposures to this product may cause serious health effects.

Carcinogen Status:

SWA: Alkanes, C3-4 is classified by SWA as a Category 1a Carcinogen

See the SWA website for further details. A web address has not been provided as addresses frequently change.

NTP: No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

Insufficient data to be sure of status.

Biodegradation is expected to be the primary fate process for aliphatic hydrocarbons in soil and water. The rate and extent of biodegradation are dependent on the ambient temperature, the presence of a sufficient number of microorganisms capable of metabolizing the hydrocarbons and the concentration in or on the soil or water.

Biodegradation of C7 to C12 hydrocarbons is expected to be significant under environmental conditions favourable to microbial oxidation. Naturally occurring hydrocarbon-degrading microorganisms have been isolated from polluted soil and, to a lesser extent, non-polluted soil.

The low water solubility and moderate vapour pressure of white spirit (Stoddard solvent) suggest that volatilization and subsequent photo-oxidation are important processes for abiotic degradation in the atmosphere.

The octanol/water partition coefficient (log Pow) of white spirit (17% v/v aromatics) has been found to be 3.5 to 6.4. This indicates a moderate potential for bioaccumulation by organisms from water and a likelihood of partitioning to fat within organisms.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle product and containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Do not puncture or incinerate aerosol cans, even when empty.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1950, AEROSOLS

Hazchem Code: 2YE

Special Provisions: 63, 190, 277, 327, 344, 381

Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

Dangerous Goods Class: Class 2.1: Flammable gases.

Packing Group: Not set

Packing Instruction: P207, LP200

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

SAFETY DATA SHEET

This version issued: October, 2022

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with AICIS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS/AIIC Australian Inventory of Industrial Chemicals
SWA Safe Work Australia, formerly ASCC and NOHSC
CAS number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020) and GHS Revision 7

Copyright © Kilford & Kilford Pty Ltd, October, 2022.

http://www.kilford.com.au/ Phone (02)8321 8866